

STAHL<sup>®</sup>

2000F-5-E Manual Rotation  
2000FR-5-E Power Rotation  
Crane Rating: 6,600 ft. lbs.  
Maximum lifting capacity: 2,000 lbs.  
Boom Length: 5' (8' & 10' optional)



### 5-FOOT BOOM REACH

Manual extension boom provides 5-ft. of reach (8-ft. and 10-ft. manual extension optional)

### COMPACT AND VERSATILE

Compact design allows mounting in service bodies, on flatbeds and in pickup beds. Floor-mount and compartment-mount models are available

### OPERATOR-FRIENDLY CONTROLS

Lightweight, multi-function remote control allows for single-handed operation of the crane

### SECURE FROM UNAUTHORIZED USE

Remote control unit can be quickly detached and locked away to prevent unauthorized use of the unit

Floor-mount model pictured

Covered by a  
1-Year Limited Warranty



Get the complete Crane and Crane Body package you need from STAHL

# LIFTING CAPACITIES\* - 2000 SERIES

REACH	RETRACTED BOOM	MANUAL EXTENSION
3 ft.	2,000 lbs.	
4 ft.		1,650 lbs.
5 ft.		1,320 lbs.

\*Double Line is required for 1,000+ lb. loads

## SPECIFICATIONS

DESCRIPTION	2000F-5-E	2000FR-5-E
Boom Rotation	Manual	Power
Total Boom Extension (Max.)	5 ft.	5 ft.
Rotation System	360° continuous manual on turntable bearing	360° continuous electric on turntable bearing with worm drive and dynamic brake
Remote Control	Lightweight removable remote control unit with 10' of cable	Lightweight removable remote control unit with 25' of cable
Winch Cable	50' of 3/16" aircraft cable with latch hook, traveling block and down-haul weight	50' of 3/16" aircraft cable with latch hook, traveling block and down-haul weight
Winch	12V - DC electric	12V - DC electric
Winch Line Speed (no load)	18.5 ft. per minute (single line)	18.5 ft. per minute (single line)
Winch Line Speed (1,000 lbs.)	12.7 ft. per minute (single line)	12.7 ft. per minute (single line)
Winch Line Speed (2,000 lbs.)	3.6 ft. per minute (double line)	3.6 ft. per minute (double line)
Rotation Speed	N/A	1 RPM
Weight	240 lbs.	260 lbs.
Storage Height Folded	51.5 in.	53 in.
Base Dimensions	12 in. x 12 in.	12 in. x 12 in.
Minimum Chassis Requirements	8,000 GVW	8,000 GVW
Power Service Requirements	12V - DC	12V - DC

## OPTIONAL EQUIPMENT:

- 8 ft. manual extension boom
- 10 ft. manual extension boom



www.anjerinc.com  
800-326-5373  
sales@anjerinc.com